

Akustikabsorber

PS WHITE

White PU film and absorbing polyurethane foam.



Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Type	Code	SELF-ADHESIVE	Rw (dB)	Weight (kg)
PS-15 sheet	26002	-	12	0,463
PS-15 A sheet	26092	x	12	0,463
PS-15 roll	26058	-	12	0,503
PS-15 A roll	26095	x	12	0,503
PS-25 sheet	26005	-	12	0,765
PS-25 A sheet	26093	x	12	0,765
PS-25 roll	26059	-	12	0,805
PS-25 A roll	26096	x	12	0,765
PS-40 sheet	26008	-	17	1,218
PS-40 A sheet	26094	x	17	1,218
PS-40 roll	26060	-	17	1,258
PS-40 A roll	26097	x	17	1,218

TECHNICAL CHARACTERISTICS

— Composition

White PU film and absorbing polyurethane foam.

— Thicknesses

15mm 25mm 40mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.

— Rolls

15mm thick, 1500mm wide x approx. 20m long
25mm thick, 1500mm wide x approx. 20m long
40mm thick, 1500mm wide x approx. 15m long

APPLICATIONS

Interior lining of soundproof cabins or vehicles where the danger of hydrocarbons or water coming in contact with the absorbent material exists.

Akustikabsorber

PS WHITE

ACOUSTIC PROPERTIES

