

# Akustikabsorber

## PSM



Black PU film, absorbing polyurethane foam and 5 Kg/m<sup>2</sup> heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Type	Code	SELF-ADHESIVE	Rw (dB)	Weight (kg.)
PSM-15 sheet	26107	-	14	6,463
PSM-15 A sheet	26101	x	14	6,463
PSM-25 sheet	26109	-	17	6,765
PSM-25 A sheet	26103	x	17	6,765
PSM-40 sheet	26111	-	20	7,218
PSM-40 A sheet	26105	x	20	7,218

### TECHNICAL CHARACTERISTICS

#### — Composition

Black PU film, absorbing polyurethane foam and 5 Kg/m<sup>2</sup> heavy viscoelastic mass.

#### — Thicknesses

15mm 25mm 40mm

### FORMATS

#### — Sheets

1200x1000 mm  
15mm thick, 8 Sheets per box.  
25mm thick, 5 Sheets per box.  
40mm thick, 3 Sheets per box.

### APPLICATIONS

Absorbent lining of soundproof cabins or vehicles where the danger of hydrocarbons or water coming in contact with the absorbent material exists and damping sheet that increases the mass and dampens vibrations.

# Akustikabsorber

## PSM

### ACOUSTIC PROPERTIES

